



**Sold & Serviced Exclusively by:**  
**BOLD Parts & Service, Inc.**  
 11933 12<sup>th</sup> Avenue South  
 Burnsville, MN 55337 USA  
 800-887-7636  
 fax 952-894-1787  
 www.boldparts.com

## Hot Melt Coating Equipment

# M107D Hot Melt Roll Coater

The M107D is designed to apply coatings for a variety of applications, including hot melt heat-activated coatings, hot melt product assembly coatings, hot melt pressure sensitive coatings and hot melt protective coatings.

The M107D has a temperature controller to prevent premature startup and the phenolic gear in the previous model has been eliminated, reducing maintenance expense.

The dual rollers on the M107D automatically feed the material through at a uniform rate and quickly apply an even honey-comb pattern of hot melt adhesive.



### Standard Features

- Temperature Controller
- Cast Aluminum Reservoir Tray w/ Integrated Heating Element
- Adjustable Top Roller
- Adjustable Doctor Blade
- Gear Motor

### Optional Equipment/Supplies

- Hand Roller
- Hot Melt Activator for reactivation of hot melt
- Hot Melt Adhesive

### Specifications

Model	M107D
Material thickness	.020" to 1-1/8"
Material width	Up to 7"
Coating Speed	70 ft per minute
Temperature – Thermostatically Controlled	200° - 500° F
Electrical requirement	120V - 60 Hz - 1 Phase - 15 Amp
Machine width x length x height	22" x 18" x 12" High
Shipping weight (approximate)	100 lbs.

Production capacities and specifications are provided for the convenience of our customers and are not binding. The manufacturer reserves the right to make changes without notice. Please contact us if the above capacities and/or specifications do not meet your requirements.

[pacehotmelt.com](http://pacehotmelt.com)

Copyright © 2016 All Rights Reserved.



## Hot Melt Coating Equipment



**Sold & Serviced Exclusively by:**  
**BOLD Parts & Service, Inc.**  
11933 12<sup>th</sup> Avenue South  
Burnsville, MN 55337 USA  
800-887-7636  
fax 952-894-1787  
www.boldparts.com

# A507C Hot Melt Activator



The A507C Hot Melt Activator provides uniform full-area heat to quickly bring heat-reactivated hot melt to its proper bonding temperature.

### Standard Features

- Infrared Heater – Glass/Ceramic Face
- Enclosed Housing for heat retention
- Heat Insulating Ceramic Base, Sides & Back
- Electrical enclosure for wiring connection

### Optional Equipment/Supplies

- M107D Hot Melt Roll Coater
- Hand Roller

### Specifications

Model	A507C
Material length	Up to 42"
Material width	Up to 7"
Temperature	800° - 900° F
Electrical requirement	240V - 1 Phase - 14 Amp / 3,360 Watts
Heater width x length x height (approximate)	9" x 43" x 15" High
Shipping weight (approximate)	50 lbs.

Production capacities and specifications are provided for the convenience of our customers and are not binding. The manufacturer reserves the right to make changes without notice. Please contact us if the above capacities and/or specifications do not meet your requirements.



Shown heating two laminate endcaps

[pacehotmelt.com](http://pacehotmelt.com)

Copyright © 2016 All Rights Reserved.